

PAC GS3 Range

Reader—HF

909022118 – PAC HF Vandal Resistant Reader - blue

The Vandal Resistant Reader is designed to work in the most demanding of operating environments as it provides a robust, intruder-graded access reader. The Vandal Resistant Reader is ideal for internal or external installations.



- Raised key symbol on the front with audible and visual user feedback for Equality Act compliance
- Comes with pre-connected 2m cable for ease of installation
- Supports the following ID Devices:
 - PAC OPS
 - PAC OPS Lite
- Integral Tamper circuit
- Reader line tamper configurable when used in conjunction with PAC 512 controllers

Part Number(s)	909022118 – PAC HF Vandal Resistant Reader - blue
Supported Credentials	PAC OPS, PAC OPS Lite
Supported Output Protocols	PAC64, PAC32, Wiegand
Audio / Visual Indicators	Audible Sounder and Red/Green LEDs
RFid Frequency	High Frequency (13.56MHz)
Maximum Read Range	40 mm / 1.57 in.
Tamper Output	Integral tamper circuit with wall sensor provided
Distance to Controller	70m / 230ft (reader powered from controller) 500m / 1,640ft (locally powered reader)
Recommended Cabling	PAC output 6-core 24 AWG 0.22m ² alarm cable (unscreened)
Power input(s)	12–24V DC, <100mA @ 12V DC
Dimensions	103 (w) x 103 (h) x 17.5 (d) mm / 4.01 (w) x 4.01 (h) x 0.69 (d) in.
Weight	0.442 kg / 0.974 lb
Material	Stainless steel grade 304
Operating Temperature	-40°C to +66°C / -40°F to 151°F
Operating Humidity	10% to 85% Relative Humidity
Warranty	Lifetime against electronic failure
Standards Compliance	UKCA, CE, FCC, IC, RoHS & WEEE compliant
Environment	IP67 – Indoor / Outdoor weather resistant
Intruder Grading	Certified to EN 50131-1 and EN 50131-3, Security Grade 3
Country of Origin	Albania